


15051 150x150x51MM



General Specifications


- ◆ Material..... Frame: Aluminum Alloy ,Impeller: Plastic(UL94V-0)
Lead Wire: UL1015 22# black Terminal:2.5mm
- ◆ Motor..... Shaded Pole & Internal Rotor Motor
- ◆ Input Voltage..... 110V/220V (optional)
- ◆ Dielectric Strength..... 50/60Hz ,1500VAC 1Min(between input terminal and frame)
- ◆ Expected Life..... Ball Bearing 50000hrs (40°C)
- ◆ Temperature Range..... Operating temperature -10°C~+70°C(Non-condensing)
Storage temperature -40°C~+70°C(Non-condensing)

Dimensions(Unit:mm)



Mounting Panel Cutout (Unit:mm)

PQ Curve(At Rated Voltage)



Safety Standards



Specifications

Model	Bearing Type	Rated Voltage	Freq	Rated Current	Input Power	Speed	Max Air Flow	Max Static Pressure	Noise	Weight
Part No.	B	VAC	Hz	Amp	Watt	RPM	CFM	Inch-H ₂ O	dB-A	g
AA15051B11HL	Dual Ball	100~120	50/60	0.24/0.21	53/47	2300/2500	150/190	0.43/0.51	52/54	950
AA15051B22HL	Dual Ball	200~240	50/60	0.24/0.21	53/47	2300/2500	150/190	0.43/0.51	52/54	950

Specifications are subject to change without notice. Please Visit our website at <http://www.szht.com> for update information.